

***Wall mounted filter for
welding fumes and light dust***

The Fumex wall mounted weld-fume filter VF is a handy equipment for temporary worksites.

The wall mounted filter VF offers a high level of filtration and high extraction capacity.

Carbon filter cartridges for gas-mixed air are available on request.

Can be equipped with an extractor arm or be connected directly to a Spiro duct.

Our recommended extractor arm is the PR arm (in a 2- or 3 meter version). This extractor has a light-weight construction with two gasprings balancing its own weight.

The smooth inside of the extraction arm helps reduce the risk of ducts being blocked.

All necessary adjustments on the extractor arm can easily be taken care of from the outside.


Extraction capacity: about 1200m³/h with PR-arm Ø 160mm.

The product can be equipped with a fan.

N.B! The portable filter is not intended for extraction of liquids!

The Fumex range also includes fans, accessories, automatic control gear and filters for extraction

LOCAL EXTRACTOR
Pure advantage



Product	a (mm)	b (mm)	c (mm)	d (mm)	e (mm)	f (mm)	Ø (mm)	Weight (kg)
VF	547	473	515	430	13	567	160	40
VF 2000	*	*	*	*	*	*	*	50
VF 3000	*	*	*	*	*	*	*	60



VF 2000 / VF 3000



VF can be ordered with or without the PR extractor to be installed directly to a Spiro duct or other installation.

VF 2000, VF 3000

Hose

Properties

Non-inflammable, suitable for welding fumes and flue gases.

Temperature range

-10°C to +90°C

Gas spring

Working temperature

+20°C

Temperature range

-40°C till +90°C

Performance

Capacity

about 1200m³/h with PR-arm Ø160mm

Filter

Filter standard
Filter accessory
Filter area

>98% acc. to DOP
Carbon filter
14m²

Other

Surface treatment of sheet metal parts.

Powder coating

Weight

40 kg

Filter house

Filter house in powder coated sheet metal

Filter

Cartridge filter, 2-layer, flame resistant.

Accessories

Carbon filter, PR 2000-160, PR 3000-160

Delivery Design

Filter is delivered assembled.