


Domekt R 600 V C6M

Maximal air flow, m ³ /h	669
Maximal air flow, l/s	186
Reference flow rate, m ³ /s	0,130
Reference pressure difference, Pa	50
SPI, W/(m ³ /h)	0,25
Thermal efficiency of heat recovery, %	84
Electric air heater capacity, kW / Δt, °C	1,5/8,9
Supply voltage, V	1~230
Maximal operating current HE, A	9,5
Power supply cable, mm ²	3×1,5
Electric power input of the fan drive at maximum flow rate, W	167
Electric power input of the fan drive at reference flow rate, W	59
Noise power level, L _{WA} , dB(A)	44
Noise pressure level, L _{PA} , dB(A), (3 m)	32
Filters dimensions B×H×L, mm	515×240×46
Unit dimensions B×H×L, mm	905×750×610
Maintenance space, mm	900
Unit weight, kg	82



Performance

Unit with standard equipment



Accessories



Closing damper	AGUJ-M-200+LF230/CM230	
Silencer	ODA/EHA	AGS-200-50-600-M
	SUP/ETA	AGS-200-50-900-M
Water heater	DH-200	
PPU	PPU-HW-3R-15-0,63-W2	
2-way valve (heater)	VVP47.15-2,5+SSF161.05HF	
Water cooler	DCW-0,5-3	
2-way valve (cooler)	VVP47.15-2,5+SSF161.05HF	
Outdoor grill	LD-200	
Water heater-cooler	DHCW-250	
DX cooler	DCF-0,5-3	
Cooling unit	MOU-12HFN8+KA8140	

Temperature efficiency

	Winter				Summer			
Outdoor temperature, °C	-23	-15	-10	-5	0	25	30	35
After heat exchanger, °C	14,8	16,1	16,9	17,7	18,5	22,5	23,2	24,1

indoor +22 °C, 20 % RH

Shown as right (R1)



Shown as left (L1)

