


Verso R 1500 U C5


Nominal air flow according to ErP 2018, m ³ /h	1634
Nominal air flow according to ErP 2018, l/s	454
Electric air heater capacity, kW / Δt, °C	4,5/7
Supply voltage HE, V	3~400
Supply voltage HW, V	1~230
Maximal operating current HE, A	12,9
Maximal operating current HW, A	6,7
Power supply cable E, mm ²	5×2,5
Power supply cable W, mm ²	3×1,5
Electric power input of the fan drive at maximum flow rate, W	450
Noise power level, L _{WA,r} dB(A)	54
Noise pressure level, L _{PA,r} dB(A), (3 m)	44
Filters dimensions B×H×L, mm	800×400×46
Unit dimensions B×H×L, mm	906×905×1355
Panel thickness, mm	50
Maintenance space, mm	800
Unit weight, kg	206



Performance

Verso R 1500 UH with standard equipment



 Does not conform to ErP2018 requirements

Accessories

Closing damper	AGUJ-M-315+LF24/LM24
Silencer	ODA/EHA AGS-315-100-900-M
	SUP/ETA AGS-315-100-1200-M
PPU	PPU-HW-3R-15-1,6-W2
Water cooler	DCW-1,4-9
2-way valve	VVP47.20-4,0+SSF161.05HF
DX cooler	DCF-1,4-10
Cooling unit	MOU 36HFN8+KA8243

Temperature efficiency

	Winter					Summer			
	Outside temperature, °C	-23	-15	-10	-5	0	25	30	35
After heat exchanger, °C	12,3	14,0	15,1	16,2	17,2	22,6	23,7	24,8	


Indoor +22 °C, 20 % RH

Changeover water/ DX heating – cooling exchanger (HCW/HCDX)


	Winter		Summer	
	Water temperature in/out, °C	60/40	7/12	–
Condensation/evaporation T, °C	–	–	45	45/5
Capacity, kW	5,2	9,5	5,2	10,8
Maximal capacity, kW	11,7	10,3	9	11,6
Pressure drop, kPa	1	10,8	–	–
Air temperature in/out, °C	12,3 / 22	30 / 18	12,3 / 22	30 / 18
Connection, " / mm	¾		½ / 22	

Summer: +30 °C/ 50 %; HCW – 1500 m³/h

Shown as right (R1)



Shown as left (L1)



▶ ODA – outdoor intake ▶ SUP – supply air ▶ ETA – extract indoor ▶ EHA – exhaust air